



QUALITY **MEETS**

EXPERIENCE



MOUNTS UNDER THE BED!

Draw-Tite Hide-A-Goose™ Gooseneck Hitch

UNRESTRICTED USE OF TRUCK BED

- Ball stores in hitch when not in use
- Below bed rail kits are vehicle specific

CLEAN INSTALLATION

- Small, 3-1/2" ball hole
- Spring loaded safety chain loops
- Vehicle Specific No Drill Rails means no cutting, welding, or bed removal

MAXIMIZE TOWING CAPACITY

- 2-5/16" chrome plated high strength steel ball
- Heavy duty handle engages and locks ball in place
- Rated for up to 30,000 lbs. GTW & 7,500 lbs. vertical load*

GOOSENECK HITCH OPTIONS AND ACCESSORIES

HI-RISE™ CONVERSION HITCH

PART	DESCRIPTION
9480	Converts an under-bed gooseneck hitch to a fifth wheel hitch

UNDER-BED

19309	2-5/16" Hitch Ball
19307	3" Ball
19306	1" Rise 2-5/16" Ball
19308	5" Offset 2-5/16" Ball
58389	Magnetic Cover

REMOV-A-BALL®

5973	2-5/16" Ball
5983	Magnetic Cover

Fold-Down Platform Head

8339



- Ball folds down when not in use
- Oversize pull ring fits a gloved hand
- Spring loaded safety chain loops
- 2-5/16" chrome plated high strength steel ball
- 3/8" thick steel top plate and substructure
- Rated for up to 25,000 lbs. GTW & 6,250 lbs. vertical load*

Remov-A-Ball® Platform Head

6300



- Remove and stow ball when not in use
- Spring loaded chromed sliding pin ensures positive lock
- Spring loaded safety chain loops
- 2-5/16" zinc plated high strength steel ball
- Large top plate footprint
- Rated for up to 30,000 lbs. GTW & 7,500 lbs. vertical load*

* Check manufacturer's vehicle weight ratings for your specific capacity. Minimum truck bed length of 6' required

GOOSENECK FIT GUIDE



Make	Years	Model	Rail Kit	Notes	Under-Bed		Above-Bed	
					Complete Kit	Head Only	Remov-A-Ball®	Fold-Down
Chevy/ GM	88-00	1500/2500, 6' & 8' Beds (Old Body Style)	4440	1	9465-40	9465	6300	8339
	99-07	1500 LD, 6' & 8' Beds (Classic)	4454		9465-54	9465	6300	8339
	07-13	1500 LD, 6' & 8' Beds (New Body style)	4454		9465-54	9465	6300	8339
	01-07	1500 HD, 6' Bed (Classic)	4454		9465-54	9465	6300	8339
	99-04	2500 LD, 6' Bed	4454		9465-54	9465	6300	8339
	99-04	2500 LD, 8' Bed	4434		9465-34	9465	6300	8339
	01-07	2500 HD, 6' & 8' Beds (Classic)	4434		9465-34	9465	6300	8339
	01-07	3500 Series (Classic)	4445		9465-45	9465	6300	8339
	07-10	2500 HD, 6' & 8' Beds (New Body style)	4434	HS	9465-34	9465	6300	8339
	07-10	3500 HD, 6' & 8' Beds (New Body style)	4434	HS	9465-34	9465	6300	8339
	11-12	2500/3500 HD, 6' & 8' Beds	4456	HS	9465-56	9465	6300	8339
Dodge	94-01	1500/2500/3500, 6' & 8' Beds	4439		9460-39	9460	6300	8339
	02-08	1500 Only, except Mega Cab	4438	LE	9464-38	9464	6300	8339
	06-08	1500 Mega Cab with 6' Bed	4435	LE	9464-35	9464	6300	8339
	09-12	1500, except Crew-Cab	4446		9464-46	9464	6300	8339
	2002	2500, 6' & 8' Beds	4439		9460-39	9460	6300	8339
	2002	3500, 8' Bed	4439		9460-39	9460	6300	8339
	03-09	2500 HD, Includes Mega Cab	4435	LE	9464-35	9464	6300	8339
	03-09	3500 HD, includes Mega Cab & Dually	4435	LE	9464-35	9464	6300	8339
	10-12	2500/3500 HD, All Beds, Inc. Mega Cab/Dually	4457	2 / LE	9464-57	9464	6300	8339
Ford	04-12	F-150, 6' & 8' Beds	4437	LE	9465-37	9465	6300	8339
	99-12	F-250/F-350 Super-Duty (exc. Cab & Chassis)	4448	LE	9460-48	9460	6300	8339
	08-12	F-450 Super-Duty (except Cab & Chassis)	4449	LE	9460-49	9460	6300	8339
Toyota	07-12	Tundra, except Crew Max with 5-1/2' Bed	4436	LE	9465-36	9465	6300	8339

Note: Rail kits and heads are not designed to be used on trucks with beds shorter than 6', or fit the Flareside/Stepside. Rail kits are rated to match manufacturers vehicle tow weight ratings. 1= Will not fit 1988-1991 4-door crew-cab models; 2= Higher load rating than 4435 rail kit; LE= May need to temporarily lower exhaust; HS= Minor heat shield modification may be required



9480



19306



19307



19308



19309