



# WARN® 9.5cti Winch Multi-Mount Contactor Equipped, with Thermometric Indicator

## The newest addition to the WARN Ultimate Performance winch lineup

- Massive protective structure combined with sophisticated operator feedback
- New contactor control features exceptional durability, extra long life, and superior weather sealing
- Series Wound motor and 3-stage planetary gear train deliver 9,500 lbs. of pulling capacity, fast line speeds, and long duty cycles
- Extreme duty winch sealing system
- Motor-mounted thermal sensor relays temperature information to winch operator by way of the hand-held remote control with LED indicator
- Redesigned remote control stands up to rough treatment off-road. Rubberized, ergonomic pistol-grip handle. Remote is ultra weather/mud resistant thanks to improved sealing. Simple, intuitive operation
- High gloss, chip-resistant black powder coat finish over a massive cast-aluminum alloy housing
- Includes 9.5cti winch, multi-mount carrier, and quick connect wiring for front of vehicle. Winch comes with 125 ft. of 5/16" wire rope, hook, remote control on 12' lead, and hawse fairlead



PN 85760 12V, Hawse  
PN 85757 H2 Hummer

The new WARN contactor is robust and reliable, and features an improved duty cycle, durable cadmium-plated copper contacts, extended heat resistance, and improved sealing (SAE 1455 rated)



The new WARN remote is constructed of durable EPDM rubber, and features enhanced switch sealing and LED indicator

## SPECIFICATIONS

**Winch model:** WARN 9.5cti Multi-Mount

**Part numbers:** PN 85760 12V, Hawse  
PN 85757 H2 Hummer

**Rated line pull:** 9,500 lbs., (4310 kgs.) single-line

**Motor:** Series Wound

**Electrical controls:** Contactor

**Remote Control:** Remote switch, LED indicator, 12' (3.7m) lead

**Geartrain:** 3-Stage Planetary

**Gear ratio:** 156:1

**Clutch (freespooling):** Sliding Ring Gear

**Brake:** Automatic Direct Drive Cone

**Drum diameter/Length:** 2.5"/9.0" (6.4cm/23cm)

**Wire rope:** 125', 5/16" diameter (38m, 8mm diam.)

**Fairlead:** Hawse

**Finish:** High-gloss powder coat over primer undercoating

**Recommended Battery:** 650 CCA minimum for winching

**Battery leads:** 2 gauge, 72" (1.83m)

### 12V DC performance specs (first layer of drum)

Line Pull Lbs. (Kgs. )	Line Speed Ft./min. (M/min.)	Motor Current	Pull by layer: layer/Lbs (Kgs.)
0	62 (18.9)	47 amps	1/9500 (4313)
2000 (910)	16.3 (4.97)	160 amps	2/8650 (3927)
4000 (1810)	11.8 (3.60)	230 amps	3/7920 (3595)
6000 (2720)	9.31 (2.84)	305 amps	4/7400 (3359)
8000 (3630)	7.59 (2.31)	370 amps	5/6940 (3150)
9500 (4310)	6.67 (2.03)	425 amps	

### Winch dimensions:

23.1" L. x 6.3" D. x 10.4" H.  
(587mm L. x 160mm D. x 264mm H.)

**Winch Weight:** 89 lbs. (36.3kgs.)

Warn Industries, Inc.  
12900 S.E. Capps Road,  
Clackamas, OR USA 97015-8903



Customer Service (North America):  
1-800-543-9276

International Sales Support:  
+1 503 722 1200

www.warn.com